

Измерители окружающей среды СО-110, СО-180, СО-181, ДТ-73С, ДТ-1307, ЛА-1017, ДТ-2232

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: mce@nt-rt.ru || сайт: <https://cem.nt-rt.ru/>



- Memory for 10 complete data sets
- LED light & audible alarm

- High Quality Sensor



EMC
EN: 61326

CO-110 Carbon Monoxide Meter detects the presence of carbon monoxide (CO) and measures concentrations between 1-1000 parts per million (PPM). The Meter indicates the presence of CO by a reading on the LCD and a beeper tone. The beeper function much like clicking of a Geiger counter: Above 200 PPM, the beeper sounds continuously with the concentration of CO. From 35 PPM to 200 PPM, the beeper sounds discontinuously with the concentration of CO.



Features

Digital LCD Display
Auto/manual zero
Memory for 10 complete data sets
Record mode
Red & Blue LED light and audible alarm
High Accuracy, quick response
Pocket size and easy to use
Fast sampling
Max Hold
Data Hold
Above 200 PPM, the beeper sounds continuously

Specifications

Operating temperature	0°C to 50.0°C
Storage temperature	-30°C to 60.0°C
Operating humidity	0-90% relative humidity (non-condensing)
Measurement Range	0 to 1000PPM
Measurement Resolution	1PPM
Accuracy	±5% or ±10PPM
Warm up period	Less than 2 seconds
Battery	9V, NEDA 1604A or equivalent
Sensor type	Stabilized electrochemical Gas-specific (CO)
Typical sensor life	3 years

Model CO-110

Size(HxWxD): 102mm x 52mm x 29mm
Weight: 84g

Accessories :
3.6V battery and Gift box with carrying case.

High quality Sensor



- Memory for 10 complete data sets
- LED light audible alarm

CO-180/181 Carbon Monoxide Meter detects the presence of carbon monoxide (CO) and measures concentrations between 1-1000 parts per million (PPM). The Meter indicates the presence of CO by a reading on the LCD and a beeper tone. The beeper function much like clicking of a Geiger counter: Above 200 PPM, the beeper sounds continuously with the concentration of CO. From 35 PPM to 200 PPM, the beeper sounds discontinuously with the concentration of CO.

Features

	CO-180	CO-181
Digital LCD Display	*	*
Auto zero	*	
Auto/manual zero	*	*
Memory for 10 complete data sets		*
Record mode		*
LED light audible alarm		*
High Accuracy, quick response	*	*
Pocket size and easy to use	*	*
Fast sampling	*	*
Max Hold	*	*
Data Hold	*	
Auto Power Off	*	*
Above 200 PPM, the beeper sounds continuously	*	*

Specifications

Operating temperature	0°C to 50.0°C
Storage temperature	-30°C to 60.0°C
Operating humidity	0-90% relative humidity (non-condensing)
Measurement Range	0 to 1000PPM
Measurement Resolution	1PPM
Accuracy	±5% or ±10PPM
Warm up period	Less than 2 seconds
Battery	9V, NEDA 1604A or equivalent
Auto Power Off	after 15 minutes of inactivity
Sensor type	Stabilized electrochemical Gas-specific (CO)
Typical sensor life	3 years

Size(HxWxD): 160mm x 56mm x 40mm

Weight: 180g

Accessories :

9V battery and Gift box with carrying case.



Model 180

Model 181



GD-3000 Flammable Gas-Leak Detector

- Audible and Visual Annunciation
- Detects: LAG, LPG, CH₄, Methane, Butane, Flammable Gas
- Catalytic Combustion Sensor

Specifications

Name	Portable gas detector		
Function	Detecting the gas leakage and absorbing static electricity		
Power consumption	DC 200mA	Battery size	1.5V x 2(AAA Size)
Detectable gas	LNG, LPG	Temperature	10°C~50°C
Humidity	95%RH or lower	Duration	About 4 hours continuously

Size(HxWxD): 164mm x 21mm

Weight: 25g

Accessories :

2 x "AAA" Alkaline Batteries and clamshell.



Model 3000

DT-73C Carbon Monoxide Meter detects the presence of carbon monoxide (CO)

Specifications			
	Range	Accuracy	Resolution
CO	0 to 1000PPM	±5% ±10PPM	1PPM

Size(HxWxD): 103mm x 54mm x 28mm **Weight:** 139g

Accessories : 3x1.5V AAA battery, Clamshell.



Model 73C

DT-1307 Solar Power Meter



Accessories :

One 12V (A23) battery and One Photo Detector.(1300,1301)
 One 9V battery and One Photo Detector.(1307/1308/1309)
 Carrying case and Gift box.

Size(HxWxD): 162mm x 63mm x 28mm
Weight: 176g

Features	
Sunlight measurement up to 1999w/m ² or 634BTU/(ft ² *h)	
High accuracy and rapid response	
Data Hold function to hold measurement values	
Unit and sign display for easy reading	
Measuring unit selection among w/m ² and BTU/(ft ² *h)	
Manual scale selection	
Direct reading with no adjustments needed	
Maximum and minimum values	
Low battery indication	

Specifications	
Display	3-1/2 digits LCD with maximum reading 1999.
Range	1999W/m ² ,634BTU/(ft ² *h)
Resolution	1W/m ² ;1BTU/(ft ² *h).
Accuracy	typically within ±10W/m ² [±3BTU/(ft ² *h)]or ±5%
Sampling time	Approx 0.25 second.

LA-1017 Solar Power Meter & DMM

Features	
Sunlight measurement up to 1999w/m ² or 634BTU/(ft ² *h)	
High accuracy and rapid response	
Data HOLD function to hold measurement values	
Unit and sign display for easy reading	
Measuring unit selection among w/m ² and BTU/(ft ² *h)	
Manual scale selection	
Direct reading with no adjustments needed	
Maximum and minimum values	
Low battery indication	

Specifications		
Function	Max Range	Basic Accuracy
Voltage DC	600V	±0.5%
Voltage AC	600V	±1.2%
Current DC	200mA	±1.5%
Current AC	200mA	±2.0%
Resistance	20MΩ	±0.8%
Continuity Test	Beep if less than 100Ω	

Solar Power Meter	
Display	3-1/2 digits LCD with maximum reading 1999.
Range	1999W/m ² ,634BTU/(ft ² *h)
Resolution	1W/m ² ;1BTU/(ft ² *h).
Accuracy	Typically within ±10W/m ² [±3BTU/(ft ² *h)]or ±5%
Sampling time	Approx 0.25 second.


Size(HxWxD): 162mm x 74.5mm x 44mm
Weight: 308g

Accessories:
 9V battery & Two "AAA" batteries, remote terminator and gift box with carrying case.

CE

EMC & LVD
 EN: 61326
 EN: 61010-1
 EN: 61010-02-032
 EN: 61010-02-033

Model 1017



22/2232 digital Multifunction Environment Meter have been designed to combine the functions of Sound Level Meter, Light Meter, Humidity Meter, and Temperature Meter. They are ideal Multifunction Environment Instruments with scores of practical applications for professional and home use.



CE

EMC & LVD
EN: 61326
EN: 61010-1,
EN: 61010-02-031



- 22: 4 in 1 environment meter. It is mini size with high technology for professional use.
- 2232: 4 in 1 multifunction environment meter with PC Interface.

Features		
	22	2232
Digital display counts	2000	4000
PC Interface		*
Auto power Off	*	*
Low battery indication	*	*

Specifications					
Function	Max Range	Resolution	Basic Accuracy	22	2232
Light	20,000Lux	0.1Lux	±0.5%±10d	*	
	40,000Lux				*
Sound	100dB	0.1dB	±3.5dB	*	
	130dB				*
Humidity	95%RH	0.1%RH	±5%RH	*	*
Temperature	1300°C	0.1°C	±3%±1d	*	
	750°C/1400°F	0.1°C/°F	±3%±2d		*

Size(HxWxD): 121mm x 60.6mm x 40mm

Weight: 280g

Accessories :

22: Rubber holster, 9V battery, Test leads and K-Type temperature probe.

2232: Rubber holster, Test leads, K-Type temperature probe, 9V battery, RS-232 PC cable & Software diskette.

Model 22

Model 2232

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +7(727)345-47-04

Беларусь +375-257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: mce@nt-rt.ru || сайт: <https://cem.nt-rt.ru/>